



PVC Braided Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
5mm	9mm	2mm	10 Bar	30 Bar	54mm	1.8kg	30 Metre
6mm	10mm	2mm	10 Bar	30 Bar	60mm	2.04kg	30 Metre
8mm	12mm	2mm	10 Bar	30 Bar	72mm	2.55kg	30 Metre
10mm	14mm	2mm	8 Bar	24 Bar	90mm	3.1kg	30 Metre
12.5mm	17mm	2.3mm	8 Bar	24 Bar	105mm	4.1kg	30 Metre
16mm	21mm	2.5mm	7 Bar	21 Bar	126mm	5.9kg	30 Metre
19mm	24mm	2.5mm	5 Bar	15 Bar	145mm	6.8kg	30 Metre
25mm	31mm	3mm	5 Bar	15 Bar	186mm	10.7kg	30 Metre
32mm	38mm	3mm	5 Bar	15 Bar	240mm	13.4kg	30 Metre
38mm	45mm	3.5mm	5 Bar	15 Bar	280mm	18.5kg	30 Metre
51mm	58mm	3.4mm	4 Bar	12 Bar	360mm	24.3kg	30 Metre

SKU - PBT

Operating Temperature

-10°C to +65°C

Peak Temperature

+70°C

Inner Layer Material

Soft Polyvinyl Chloride (PVC)

Reinforcement

Triple Polyester Yarn

Outer Layer Material

Soft Polyvinyl Chloride (PVC)

Standard

ISO 5774: 2016 TYPE A

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.