



SKU - PCT

Operating Temperature
-10°C to +65°C

Peak Temperature
+70°C

Inner Layer Material
Soft Polyvinyl Chloride (PVC)

Reinforcement
None

Outer Layer Material
Soft Polyvinyl Chloride (PVC)

Standard
GB/T 13527.1-92

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

HOSESUK
WHOLESALE

PVC Unreinforced Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
3mm	5mm	1mm	1.5 Bar	4.5 Bar	20mm	0.58kg	30 Metre
4mm	6mm	1mm	1.5 Bar	4.5 Bar	24mm	0.64kg	30 Metre
5mm	7mm	1mm	1.5 Bar	4.5 Bar	30mm	0.76kg	30 Metre
6mm	8mm	1mm	1.5 Bar	4.5 Bar	36mm	0.90kg	30 Metre
8mm	10mm	1mm	1.5 Bar	4.5 Bar	48mm	1.15kg	30 Metre
10mm	13mm	1.5mm	1.5 Bar	4.5 Bar	60mm	2.20kg	30 Metre
12mm	15mm	1.5mm	1 Bar	3 Bar	72mm	2.60kg	30 Metre
16mm	19mm	1.5mm	1 Bar	3 Bar	96mm	3.40kg	30 Metre
19mm	22.5mm	1.8mm	1 Bar	3 Bar	120mm	4.60kg	30 Metre
22mm	25.5mm	1.8mm	1 Bar	3 Bar	150mm	5.30kg	30 Metre
25mm	29mm	2mm	1 Bar	3 Bar	180mm	6.90kg	30 Metre

Hose Distribution. Simplified.