



PVC Corrugated Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
19mm	23mm	2mm	5 Bar	15 Bar	70mm	4.1kg	30 Metre
25mm	30mm	2.6mm	5 Bar	15 Bar	70mm	9.5kg	50 Metre
28mm	33mm	2.5mm	4 Bar	12 Bar	80mm	11kg	50 Metre
32mm	38mm	3mm	4 Bar	12 Bar	90mm	11.9kg	50 Metre
38mm	44mm	3mm	3 Bar	9 Bar	110mm	14kg	50 Metre
40mm	46mm	3mm	3 Bar	9 Bar	150mm	14.7kg	50 Metre
50mm	58mm	4mm	3 Bar	9 Bar	170mm	23.5kg	50 Metre

SKU - PDH - Black
CDH - Clear

Operating Temperature
-10°C to +65°C

Peak Temperature
+70°C

Inner Layer Material
Smooth Polyvinyl Chloride (PVC)

Reinforcement
High Tensile Plastic Rib

Outer Layer Material
Corrugated Polyvinyl Chloride (PVC). UV Resistant.

Standard
BS EN ISO 3994-2001

Colour
● ○

View Product Online

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.