



SKU - PLH

Operating Temperature
-10°C to +65°C

Peak Temperature
+70°C

Inner Layer Material
Black Polyvinyl Chloride (PVC)

Reinforcement
Triple Polyester Yarn

Outer Layer Material
Polyvinyl Chloride (PVC)

Standard
ISO 5774: 2016 TYPE C

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

HOSESUK

WHOLESALE

PVC LPG Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
5mm	11mm	3mm	20 Bar	60 Bar	55mm	10.2kg	100 Metre
6mm	12mm	3mm	20 Bar	60 Bar	60mm	11.5kg	100 Metre
8mm	15mm	3.5mm	20 Bar	60 Bar	75mm	17kg	100 Metre
10mm	17mm	3.5mm	20 Bar	60 Bar	85mm	20kg	100 Metre
13mm	21mm	4mm	20 Bar	60 Bar	105mm	28.8kg	100 Metre

Hose Distribution. Simplified.