



Polyurethane PU Ducting

Inside Diameter	Outside Diameter	Wall Thickness	Negative Pressure	Bending Radius	Coil Weight	Coil Length
50mm	60mm	0.4mm	-0.20 Bar	32mm	7.7kg	20 Metre
65mm	75mm	0.4mm	-0.17 Bar	55mm	9.8kg	20 Metre
80mm	90mm	0.4mm	-0.16 Bar	65mm	14.2kg	20 Metre
100mm	110mm	0.4mm	-0.13 Bar	85mm	7kg	10 Metre
125mm	135mm	0.4mm	-0.01 Bar	105mm	8.9kg	10 Metre
150mm	160mm	0.4mm	-0.08 Bar	125mm	11.5kg	10 Metre
160mm	170mm	0.4mm	-0.06 Bar	135mm	12kg	10 Metre
180mm	190mm	0.4mm	-0.05 Bar	145mm	12.5kg	10 Metre
200mm	210mm	0.4mm	-0.04 Bar	165mm	13.5kg	10 Metre

SKU - PUD

Operating Temperature

-40°C to +90°C

Peak Temperature

+125°C

Inner Layer Material

Semi-Transparent
Polyurethane (PU)

Reinforcement

Copper Plated Left Hand
Spiral Steel Wire, Anti Static

Outer Layer Material

Semi-Transparent
Polyurethane (PU)

Standard

TRBS2153

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.