

Rubber LPG Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
5mm	12mm	3.5mm	20 Bar	60 Bar	72mm	17kg	100 Metre
6mm	13mm	3.5mm	20 Bar	60 Bar	78mm	18kg	100 Metre
8mm	15mm	3.5mm	20 Bar	60 Bar	90mm	20kg	100 Metre
10mm	17mm	3.5mm	20 Bar	60 Bar	102mm	24.5kg	100 Metre
13mm	21mm	4mm	20 Bar	60 Bar	126mm	32kg	100 Metre

SKU - RLH

Operating Temperature
-20°C to +85°C

Peak Temperature
+100°C

Inner Layer Material
Black Smooth Oil Resistant
Synthetic Rubber

Reinforcement
High Tensile Fabric Layers

Outer Layer Material
Orange Weather Resistant
Synthetic Rubber

Standard
ISO 3821 / BS 3212/2

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.