



Rubber Unreinforced Fuel & Oil Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
3mm	7mm	2mm	5 bar	15 bar	28mm	4.71kg	100 Metre
4mm	8mm	2mm	5 bar	15 bar	32mm	5.65kg	100 Metre
5mm	9mm	2mm	5 bar	15 bar	36mm	6.15kg	100 Metre
6mm	10mm	2mm	5 bar	15 bar	40mm	7.53kg	100 Metre
8mm	13mm	2.5mm	5 bar	15 bar	52mm	11.53kg	100 Metre
10mm	15mm	2.5mm	5 bar	15 bar	60mm	13.73kg	100 Metre

SKU - RUH

Operating Temperature
-20°C to +100°C

Peak Temperature
+120°C

Inner Layer Material
Black Smooth Oil Resistant
NBR Nitrile Rubber

Reinforcement
None

Outer Layer Material
Black Smooth Oil Resistant
NBR Nitrile Rubber

Standard
BS EN ISO 11424-2007

Colour
●

[View Product Online](#)

Hoses UK
Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:
01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.