



Rubber Wire Reinforced Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
13mm	24mm	5.5mm	10 Bar	30 Bar	144mm	9.6kg	20 Metre
16mm	27mm	5.5mm	10 Bar	30 Bar	162mm	11.1kg	20 Metre
19mm	30mm	5.5mm	10 Bar	30 Bar	180mm	12.7kg	20 Metre
22mm	33mm	5.5mm	10 Bar	30 Bar	198mm	14.2kg	20 Metre
25mm	36mm	5.5mm	10 Bar	30 Bar	216mm	15.8kg	20 Metre
28mm	38mm	5mm	10 Bar	30 Bar	228mm	17.4kg	20 Metre
32mm	42mm	5mm	10 Bar	30 Bar	252mm	19.4kg	20 Metre
35mm	45mm	5mm	10 Bar	30 Bar	270mm	21kg	20 Metre
38mm	48mm	5mm	10 Bar	30 Bar	288mm	22.5kg	20 Metre
45mm	57mm	6mm	10 Bar	30 Bar	342mm	26.2kg	20 Metre
51mm	63mm	6mm	10 Bar	30 Bar	378mm	29.3kg	20 Metre

SKU - RWR

Operating Temperature

-20°C to +80°C

Peak Temperature

+85°C

Inner Layer Material

Black Smooth Synthetic SBR Rubber

Reinforcement

2 Ply Fabric Cords With One Steel Wire Spiral

Outer Layer Material

Black Smooth Synthetic SBR Rubber

Standard

SAE J20R3

Colour ●

[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.