



SKU - SRP

Operating Temperature
-50°C to +220°C

Peak Temperature
+250°C

Inner Layer Material
Smooth Extruded Silicone Compound

Reinforcement
Polyester Braid

Outer Layer Material
Silicone

Standard
SAEJ20R3

Colour
● ●

[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

HOSESUK
WHOLESALE

Silicone Reinforced End Cap

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Overall Length	Insertable Length	Weight
4mm	12mm	4mm	12 Bar	36 Bar	60mm	50mm	6g
6mm	14mm	4mm	11 Bar	33 Bar	60mm	50mm	10g
8mm	16mm	4mm	11 Bar	33 Bar	60mm	50mm	10g
10mm	18mm	4mm	9 Bar	27 Bar	60mm	50mm	11g
12mm	20mm	4mm	8 Bar	24 Bar	60mm	50mm	15g
16mm	24mm	4mm	7 Bar	21 Bar	60mm	50mm	17g
18mm	26mm	4mm	6 Bar	18 Bar	60mm	50mm	19g
20mm	28mm	4mm	5 Bar	15 Bar	60mm	50mm	20g
25mm	33mm	4mm	5 Bar	15 Bar	60mm	50mm	34g

Hose Distribution. Simplified.