



Silicone Wire Reinforced Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
6mm	16mm	5mm	10 Bar	30 Bar	96mm	0.17kg	1 Metre
8mm	18mm	5mm	10 Bar	30 Bar	104mm	0.22kg	1 Metre
9.5mm	19.5mm	5mm	10 Bar	30 Bar	122mm	0.26kg	1 Metre
13mm	23mm	5mm	10 Bar	30 Bar	144mm	0.35kg	1 Metre
16mm	26mm	5mm	10 Bar	30 Bar	162mm	0.41kg	1 Metre
19mm	29mm	5mm	10 Bar	30 Bar	180mm	0.42kg	1 Metre
22mm	32mm	5mm	10 Bar	30 Bar	198mm	0.49kg	1 Metre
25mm	35mm	5mm	10 Bar	30 Bar	216mm	0.52kg	1 Metre
28mm	38mm	5mm	10 Bar	30 Bar	228mm	0.57kg	1 Metre
30mm	40mm	5mm	10 Bar	30 Bar	252mm	0.66kg	1 Metre
32mm	42mm	5mm	8 Bar	24 Bar	270mm	0.73kg	1 Metre
35mm	45mm	5mm	8 bar	24 Bar	288mm	0.84kg	1 Metre

SKU - SWR

Operating Temperature
-50°C to +250°C

Peak Temperature
+250°C

Inner Layer Material
Smooth Extruded Silicone Compound

Reinforcement
Polyester Braids & Steel Wire Helix

Outer Layer Material
Silicone

Standard
SAEJ20R3

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.