



PVC Wire Reinforced Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
10mm	16mm	3mm	12 Bar	36 Bar	102mm	15.9kg	100 Metre
13mm	19mm	3mm	10 Bar	30 Bar	126mm	17kg	100 Metre
16mm	22mm	3mm	10 Bar	30 Bar	150mm	26kg	100 Metre
19mm	26mm	3.5mm	7 Bar	20 Bar	156mm	17.7kg	50 Metre
25mm	33mm	3.5mm	7 Bar	20 Bar	192mm	25.3kg	50 Metre
32mm	42mm	3.5mm	6 Bar	18 Bar	234mm	35kg	50 Metre
38mm	49mm	3.5mm	5 Bar	15 Bar	270mm	42kg	50 Metre
51mm	65mm	3.5mm	3 Bar	9 Bar	348mm	51kg	50 Metre

SKU - WPH

Operating Temperature
-10°C to +65°C

Peak Temperature
+70°C

Inner Layer Material
Polyvinyl Chloride (PVC)

Reinforcement
Galvanized Steel Wire Spring

Outer Layer Material
Polyvinyl Chloride (PVC)

Standard
BS EN 10324-2005

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.