



SKU - WSH

Operating Temperature
-50°C to +250°C

Peak Temperature
+250°C

Inner Layer Material
Silicone Extruded
Flourosilicone Compound

Reinforcement
Polyester Braids

Outer Layer Material
Silicone Cloth Wrap

Standard
SAEJ20R6

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

HOSESUK
WHOLESALE

Silicone Wrapped Fuel & Oil Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Number Of Ply	Coil Weight	Coil Length
13mm	22mm	4.5mm	8.3Bar	27 Bar	3	0.26kg	1 Metre
16mm	25mm	4.5mm	7.1 Bar	25 Bar	3	0.30kg	1 Metre
19mm	28mm	4.5mm	6.5 Bar	19.5 Bar	3	0.31kg	1 Metre
25mm	34mm	4.5mm	5.5 Bar	16.5 Bar	3	0.37kg	1 Metre
32mm	41mm	4.5mm	5.1 Bar	15.5 Bar	3	0.50kg	1 Metre
35mm	44mm	4.5mm	5 Bar	15 Bar	3	0.54kg	1 Metre
38mm	47mm	4.5mm	5 Bar	15 Bar	3	0.60kg	1 Metre
45mm	54mm	4.5mm	4.6 Bar	14 Bar	3	0.71kg	1 Metre
51mm	62mm	5.5mm	4.5 Bar	13.5 Bar	4	0.94kg	1 Metre

Hose Distribution. Simplified.